

DESIGNER INFORMATION



For joint details, see PV-101.

For curb details, see Detail 'G'.


All transverse bars are #5.

Use epoxy coated bars for all reinforcement.


Quantities for both the 1'-9" top part of the sleeper slab and the 6'-3" portion under the approach pavement have been included in the double reinforced section quantities.



SECTION A-A



SECTION B-B





APPROACH PAVEMENT LAYOUT AT A SKEW

Pay limits for contract item include the following areas:




- Double Reinforced Section
- Sleeper Beam Section
- Single Reinforced Section
- Non-Reinforced Section

Possible Contract Item:  
Bridge Approach, BR-205  
Longitudinal Grooving in Concrete, Bridge Deck  
Longitudinal Grooving in Concrete, Pavement



Possible Tabulation:  
112-6

		REVISION	
		10	10-21-25
<b>STANDARD ROAD PLAN</b>		<b>BR-205</b>	
REVISIONS: Changed 'KT' joints to BT joints.		SHEET 1 of 4	
			
APPROVED BY DESIGN METHODS ENGINEER			
<b>DOUBLE REINFORCED 12" APPROACH (SLAB BRIDGE)</b>			






15 If abutting pavement (PCC or HMA) is not in place, refer to BR-213.



<b>IOWA DOT</b> <b>STANDARD ROAD PLAN</b> REVISIONS: Changed 'KT' joints to BT joints. APPROVED BY DESIGN METHODS ENGINEER <b>DOUBLE REINFORCED 12" APPROACH (SLAB BRIDGE)</b>	REVISION	
	10	10-21-25
	<b>BR-205</b>	
	SHEET 3 of 4	



16 Joint at end of Bridge Rail End Section: Place joint filler the full depth of the bridge approach pavement. In areas with curb, place full depth of pavement plus curb and shape material to fit the shape of the curb per Section B-B of PV-101. Seal joint per Detail F of PV-101.


- Fixed Abutment Bridges: Type 'E' Joint.
- Moveable Abutment Bridges: Flexible Foam Expansion Joint Filler complying with Section 4136 of the Standard Specifications. Set width of gap to 2 inches. Joint length as required to completely fill from back side of curb to front face of bridge wing.

17 Edge with 1/4 inch tool for length of joint indicated if formed edging not required when cut with diamond blade saw.

18 Compact tire buffings by spading with a square-nose shovel. Tire buffings shall not be larger than 1/2 inch.


19 Setting Width Notes:

- Width is perpendicular to abutment.




'BE'JOINT  
DETAIL

Table 1
Approved List of Sealant
Dow - Dowsil 902 RCS
Sika - Sikasil 728 RCS
Watson Bowman Acme - Wabo SiliconeSeal
Pecora - 322FC



DETAIL 'G'



DETAIL 'E'  
(Back of Curb Placement)

<b>IOWA DOT</b> <b>STANDARD ROAD PLAN</b>	REVISION	
	10	10-21-25
<b>BR-205</b> SHEET 4 of 4		
REVISIONS: Changed 'KT' joints to BT joints.		
APPROVED BY DESIGN METHODS ENGINEER		
<b>DOUBLE REINFORCED 12" APPROACH (SLAB BRIDGE)</b>		